

ATHENA

CRAWLER SELF-LEVELLING SCISSOR LIFT



850-BL
870-BL
1090-BL

850-HE
1090 PRIMO



ALMACRAWLER

Technical data

Basket capacity	250 kg (2 op.)
Basket size	1.50 x 0.78 m
Max working height	7.9 m
Max height basket floor	5.9 m
Moving height	6.0 m
Accelerator	Automatic
Undercarriage	Bi-Levelling
Basket levelling	Automatic
Longitudinal levelling Front	+/- 16°
Longitudinal levelling Rear	+/- 20°
Lateral levelling	+/- 15°
Electric pump (option)	220V-2,2kW
Direction-Control System	Yes
Easy-Drive System	Yes
Max speed	max 2.20 km/h
Ground emergency	Yes
Control of inclination	Automatic
Gradeability	25°
Side slope	21°
Length	1.94 m
Width	1.30 ÷ 1.50 m
Min height with narrow tracks (folded railings)	2.28 (1,98) m
Min height with wide tracks (folded railings)	1.98 (1,68) m
Compliance	EN 280, ANSI, CSA, AS/NZS

Version

HE	-
BL	Gasoline Honda iGX390 Diesel YANMAR 2TNV70-ASA 13.8 HP
EVO	2070 kg / 2090 kg Diesel Kubota Z482
PROACTIVE LEVELLING	
DYNAMIC LEVELLING	2450 kg
EVO BI-ENERGY	-
PROACTIVE LEVELLING	
DYNAMIC LEVELLING	
PRiMO FULL ELECTRIC ELECTRIC DRIVE	-
PROACTIVE LEVELLING	
DYNAMIC LEVELLING	

850-BL

ATHENA 850-BL 850-BL EVO

